



## BWB SERIES AND MS1414

The many different features of the WIDE BODY SAFES, make them perfect for commercial application or home use.

**Order for Oren Locksmith: Eli Fishman 323 931-9966**

**MS1414K with**

**Slot open option**



**MS1414K WITH  
SLOT OPTION**

### **Mini Safe (MS Series) Features:**

- Strong, formed "B" Rate construction made of A36 solid steel plate for improved security and appearance.
- Formed door jamb for increased resistance to sledgehammer attack.
- ½" solid steel door.
- U.L. Group II combo lock (C), U.L. listed dual nose keylock (K).
- Three 1" diameter chromed steel locking bolts.
- Bolt detent system engages boltwork automatically.
- Auxiliary spring-loaded relocking device.
- Lock and relock protected by large carburized hardplate.
- Four anchor bolt holes with hardware.
- Adjustable shelf provided.
- Also available with optional deposit slot. (shown above) Slot size: ½" H x 6 W"



## Amsec DSF2014K Depository Safe



AMSEC's DS series depository safes are designed to provide immediate deposits and secure storage for cash, jewelry, and miscellaneous valuables. Drops can be made through a front-loading deposit door.

### Features:

- U.L. listed dual nose keylock
- Three 1" diameter chromed steel locking bolts.
- Auxiliary spring-loaded relocking device.
- Front-Load Hopper Size: 4"D x 2"W x 9-3/4"L
- Strong, formed "B" Rate construction made of A36 solid steel plate for improved security and appearance.
- Formed door jamb for increased resistance to sledgehammer attack.
- Four anchor bolt holes are standard.

Inside: 10" x 13 3/4" x 11"

Outside: 20 1/4" x 14" x 14"

Weight: 79 lbs.

Cubic In. Capacity: 1,513

### "B" Rated - Front Loading Depository Safes

Amsec's new series of depository safes are designed to provide immediate and secure storage for cash, jewelry and miscellaneous valuables. When the door is locked, deposits can be made via a front loading deposit door. Instant protection from hold-up or burglary!!

Door: 1/2" thick A36 solid steel plate, to increase resistance to pry attack.

3-way boltwork with three 1" round plated bolts. Metal shear point handle. Auxiliary spring loaded relocking devices. Lock & relocks protected by large carbonized hardplate.

Body: Formed "B" rate construction made of A36 solid steel plate for improved security and appearance. Door jamb formed from body for increased resistance to sledgehammer attack.

Front Load Hopper: 3" D x 4 1/2" H x 10 1/2" L. Recessed, heavy duty 3/16" construction, (1/4" door). Protected by dual "Anti-Fish" baffles.

4 Pre-drilled anchor holes.